

TRITON SPRAY SYSTEM \

PORTABLE

Proprietary Spray Gun:

Pneumatic trigger, custom aluminum body, and patent-pending stainless steel spray tips engineered specifically for Triton's proprietary, instant-set liquid rubber technology. Our spray gun has a lightweight, durable handle with separate valve controls and quick link disconnects. The gun was designed in-house and is 100% American-made, with even the smallest parts machined at Triton's factory.

Unit Assembly:

- 25 ft. (7.5 m) cloth-covered hose
- Stainless steel, quick disconnect fittings
- Push-lock fittings for air and accelerator
- Collapsible handle for easy transportation
- DeWalt 120 Volt air compressor, oil-free
- Polypropylene accelerator tank with graduations
- Custom-machined mounting plate for pumps with handles
- Custom quick-release tank mounts of easy disassembly

Weight/Dimensions:

- System Weight: 100 lbs. (45 kg) fully loaded
- System Dimensions: 33" L x 24"W x 26"H (in operating position)

Pumps & Cleaning:

Both accelerator and product pumps are industrial-grade 100 psi air-driven diaphragm pumps with Viton seals and polypropylene check valves. Both pumps are easily flushed with soap and water, no harmful solvents needed. They are easily removed with or without the accelerator tank, as needed. The pumps are driven by the on-board electric air compressor and are controlled with simple ball valves for ease of use and reliability.

