

TRITON SPRAY SYSTEM \

STANDARD

Instant-Set Spray System:

Pneumatic trigger, custom aluminum body, and patent-pending stainless steel spray tips engineered specifically for Triton's proprietary, instant-set liquid rubber technology. Our spray gun has a lightweight, durable handle with separate valve controls and quick link disconnects. The gun was designed in-house and is 100% American-made, with even the smallest parts machined at Triton's factory.

Cart & Hose Assembly

- 150 ft. (45 m) hose, with maximum of 300 ft.
- Stainless steel, quick disconnect fittings
- Push-lock fittings for air and accelerator
- Protective cloth cover on hose
- Proprietary, user-friendly steel frame design
- Black powder coating for protection
- Control box provides easy access to gauges and fittings

Weight/Dimensions:

- System Weight: 230 lbs. (104 kg) fully loaded
- System Dimensions: 51" H x 28"D x 26"W

Pumps & Cleaning:

Main product pump is an industrial, air-driven diaphragm pump with 300 psi spray pressure. This pump is easily cleaned with soap and water, no harmful solvents needed.

It is conveniently located on top of the cart and does not need removed for cleaning. The accelerator pump is a 100 psi air-driven diaphragm pump and is flushed with only water.

The entire spray system is driven by an air compressor with a minimum 18 CFM capability.

