

PRODUCT CATALOG

<i>Product</i>	<i>Description</i>
TRITOFLEX Liquid Rubber Membrane	
2K Instant-Set	FM-Approved, instant-setting, two-component, liquid rubber membrane; water-based and cold spray-applied to any thickness in one coat. The world's premier seamless membrane.
1K S (Spray-Grade)	Single-component liquid rubber membrane, water-based and VOC-free, applied with conventional airless spray equipment.
1K B (Brush-Grade)	Brush-applied, synthetic rubber mastic for patching, repairs, flashing, and other applications.
TRITOCRYL Acrylic Coating	
1K Acrylic	Water-based acrylic elastomeric roof coating applied by roller, airless sprayer, or brush. Available in white, gray, and tan, or can be custom tinted to any color.
2K Instant-Set	FM-Approved, instant-setting, two-component, water-based acrylic roof coating; applied to any thickness in one coat.
Repair Mastic	Water-based acrylic repair mastic for patching TritoCryl 1K or 2K.
LIQUID ACCESSORIES	
Polyester Fabric	Non-woven polyester fabric, available in various widths up to 40".
All-Weather Roof Patch	Water-free, synthetic rubber compound used for roof repairs in all weather conditions, including freezing temperatures and wet surfaces.
TritoWalk Walkway Coating	Seamless, anti-slip coating made with acrylic polymers and silica sand. Available in yellow or gray. Used to create walkways and safety lines.
Ceramic-Coated Roof Granules	Used for granulated top coats or granulated roof walkways.
Pump Cleaner	Concentrated pump flushing fluid for the Triton spray rigs.
SPRAY EQUIPMENT	
High Production Instant-Set Electric Spray Rig	Proprietary instant-set spray system for TritoFlex 2K and TritoCryl 2K products; includes pumps, 300 ft. (450' option) of hose, and spray gun; applies at 4 gpm rate for faster production speeds.
PVC Slip-Resistant* Single-Ply Membrane	
Triton Protan SE PVC	Premium thermoplastic polyvinyl chloride membrane, engineered with a high wet Coefficient of Friction surface to enhance safety and reduce the likelihood of roof-top slips and falls. FM-Approved and installed on over 1 billion square feet. Polyester-reinforced, 72 mil thickness.
Triton Protan EX PVC	Fleeceback version of the SE PVC membrane