

THE 4 R's

REPAIR - \$

- Short-term patches and bandages to stop leaks
- TritoFlex 1K or 2K Rubber is used extensively to repair leaking roofs, seal ductwork, and more. The Rubber can then be top coated with either granules or one of our top coats.

RESTORE - \$\$

- Protect existing roof membrane from further UV damage with repairs and a reflective coating
- Roof restoration involves applying our industrial-grade, non-toxic TritoFlex Synthetic Rubber waterproofing material on all seams, flashings, fasteners, drains, transitions, etc. at 60-80 dry mils to waterproof and seal off all deficiencies
- TritoCryl 2K instant-set white protective coating applied over entire roof as a new, reflective, sacrificial coating to extend the life of the existing roof.
- Warranties of 10 or 15-years are renewable, simply with touch-up and recoat

RECOVER - \$\$\$

- Complete, new seamless waterproofing membrane installed over the old roof
- Some roofs simply need a new membrane. TritoFlex 2K Rubber is applied directly to the old roof to create a new seamless waterproofing membrane that is resistant to hail, ponding water, foot traffic, punctures, and very high wind speeds. With the warranty to back it.
- Avoids the conventional recover approach of holding down a single-ply with thousands of screws or expensive and smelly glues
- NDL Warranties of 15 or 20-years, which are also renewable

REPLACE - \$\$\$\$

- Tear-off existing roof to the deck, installing new insulation and membrane system
- While it is common practice to replace with a single-ply or two-ply rolled product, TritoFlex 2K Rubber can be used as a vapor barrier and as the new membrane when a tear-off is inevitable.